

Date of revision: 20/07/2020

Section 1: Identification of the substance/mixture					
Code	N/A				
Product Name	Bottle Blonde Powder Lightener				
Recommended Use	Bleaching powder for hair (cosmetic use)				
Company Details	Evo Labs Pty Ltd				
Address	17-21 Commercial St Marleston, South Australia, Australia 5000				
Telephone Number	+61 8 8403 8263				
Email	compliance@evohair.com				
Emergency Telephone Number	 Australia Poison Information centre: Phone 13-11-26 New Zealand: National Poison Information centre. Phone 0800-764-766 Ospedale Niguarda Ca' Granda - Milano - 02/66101029 Azienda Ospedaliera S.G.Battista - Molinette - Torino - 011/6637637 Clinica Del Lavoro E Della Riabilitazione- Pavia - 0382/24444 Università Degli Studi Di Padova - Padova - 049/8275078 04 Istituto Scientifico G. Gaslini - Genova - 010/5636245 Azienza Ospedaliera Careggi - Firenze - 055/4277238 Policlinico A.Gemelli - Univ. Cattolica Del Sacro Cuore - Roma - 06/3054343 Centro Antiveleni - Università La Sapienza - Roma - 06/49970698 Centro Antiveleni Azienda Ospedaliera A. Cardarelli - Napoli - 081/7472870 Global Links to Poison Centres and Clinical Toxicologists all over the World: http://www.eapcct.org/index.php?page=links 				



Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener Version no.: 2 Date of revision: 20/07/2020

Section 2: Hazards Identification

Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazchem Classification and indication

Oxidising solid, category 3 Acute toxicity, category 4 Skin corrosion, category 1B		May intensify fire; oxidiser Harmful if swallowed Causes severe skin burns and eye damage
Serious eye damage, category 1	H318	Causes serious eye damage
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation
Respiratory sensitization, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
Skin sensitization, category 1	H317	May cause an allergic skin reaction

Label Elements

Hazard Pictograms

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements

Signal Words

Danger

Hazard Statements

May intensify fire; oxidiser.



Page 3 of 23

Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener Version no.: 2 Date of revision: 20/07/2020

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing
	difficulties if inhaled.
H317	May cause an allergic skin reaction.
1017	
Precautionary statements	
P210	Keep away from heat, hot surfaces, sparks, open flames and
	other ignition sources. No smoking.
P220	Keep away from clothing and other combustible materials.
P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/ protective clothing / eye protection /
	face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated
	clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: remove person to fresh air and keep
	comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue
	rinsing.
P310	Immediately call a POISON CENTER / doctor /
Contains	DISODIUM METASILICATE
	SODIUM SILICATE
	DIPOTASSIUM PEROXODISULPHATE
	AMMONIUM PEROXYDISULPHATE
	SODIUM PERSULFATE

Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%

Section 3: Composition/information on ingredients

Substances



Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener

Information not relevant

Mixtures

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification	x = Conc. %	Classification 1272/2008 (CLP)
DIPOTASSIUM PEROXODISULPHATE CAS 7727-21-1 EC 231-781-8 INDEX 016-061-00-1 Reg. no. 01-2119495676-19-0000	25 ≤ x < 50	Ox. Sol. 3 H272, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317
SODIUM SILICATE CAS 1344-09-8 EC 215-687-4 INDEX – Reg. no. 01-2119448725-31-0011	10 ≤ x < 25	Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335
AMMONIUM PEROXYDISULPHATE CAS 7727-54-0 EC 231-786-5 INDEX 016-060-00-6 Reg. no. 01-2119495973-19-0000	10 ≤ x < 25	Ox. Sol. 3 H272, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317
SODIUM PERSULFATE CAS 7775-27-1 EC 231-892-1 INDEX - Reg. no. 01-2119495975-15-0000	5 ≤ x < 10	Ox. Sol. 3 H272, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317
DISODIUM METASILICATE CAS 6834-92-0 EC 229-912-9 INDEX 014-010-00-8 Reg. no. 01-2119449811-37-xxxx	5 ≤ x < 10	Met. Corr. 1 H290, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335

Section 4: First Aid Measure



Version no.: 2 Date of revision: 20/07/2020

Description of first aid measure	Swallowed: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.				
	Eyes: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.				
	Skin: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.				
	Inhaled: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.				
	Seek medical advice or phone National Poison Information Centre Australia: Phone 13-11-26 (or) New Zealand: Phone 0800-764766				
	Global: <u>http://www.eapcct.org/index.php?page=links</u>				
Notes for medical personal	Treat on the basis of symptoms.				
Acute	Specific information on symptoms and effects caused by the product are unknown.				

Section 5: Fire-Fighting measures

Fire hazard properties	Hazards caused by exposure in the event of fire: If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.
Extinguishing media & methods	Extinguishing substances are carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak. UNSUITABLE EXTINGUISHING EQUIPMENT Do not use jets of water.



Version no.: 2 Date of revision: 20/07/2020

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire if it is safe to do so.

Protection Equipment for Firefighters

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

Section 6: Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures	If there are no contraindications, spray powder with water to prevent the formation of dust. Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.
Environmental precautions	The product must not penetrate into the sewer system or come into contact with surface water or ground water.
Methods and material for containment and cleaning up	Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues. Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.
Reference to other sections	Any information on personal protection and disposal is given in sections 8 and 13.



Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener Version no.: 2 Date of revision: 20/07/2020

Section 7: Handling and Storage

Subsection 1	
Safe Handling Practices	Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink, or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.
Subsection 2	
Safe Store site requirements	Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.
	Store in cool (below 30 °C) and dry areas. Avoid contamination and avoid the presence of reducing agents like lotions and permanent waves. Discard any unused mixture with developer or bleaching lotions, since the container may break. AVOID humid organic material as paper towel, wood, clothes, etc. which could induce spontaneous combustion. Protect from heat and sunlight; store in places far from rain and humidity; never store outdoors. Store separately from other dangerous and incompatible substances.

Section 8: Exposure Control/Personal Protection

Control parameters

Regulatory	References:	
ESP	España TLV-ACGIH	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2015 ACGIH 2016

DIPOTASSIUM PEROXODISULPHATE		
Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,0763	mg/l
Normal value in marine water	0,011	mg/l
Normal value for fresh water sediment	0,275	mg/kg
Normal value for marine water sediment	0,0396	mg/kg
Normal value for water, intermittent release	0,763	mg/l
Normal value of STP microorganisms	3,6	mg/l
Normal value for the terrestrial compartment	0,015	mg/kg



Date: 06/12/2018

Product name: Bottle Blonde Powder Lightener

Version no.: 2 Date of revision: 20/07/2020

Health - De	erived no-eff	ect level - Di							
neann - De	Effects on	ect level - Di			Effects on workers				
Route of	consumers Acute local	Acute	Chronic	Chronic	Acute local	Acı	Ite	Chronic	Chronic
exposure	/ louio loodi	systemic	local	systemic	/ louio looul		temic	local	systemic
Oral		30 mg/kg bw/d		9,1 mg/kg bw/d					,
Inhalation	295 mg/m3	295 mg/m3	1,03	1,03		590) mg/m3	2,06	2,06
			mg/m3	mg/m3			3 ,	mg/m3	mg/m3
Skin	1,124	200 mg/kg	0,051	9,1 mg/kg	2,248	400) mg/kg	0,102	18.2 mg/kg
	mg/cm2	bw/d	mg/cm2	bw/d	mg/cm2	bw/	/d	mg/cm2	bw/d
	M PEROXYD	ISULPHATE							
Threshold I	_imit Value								
Туре		C	Country	TWA/8h			STEL/1	5min	
				mg/m3	ppm				ppm
VLA		E	SP	0,1					
TLV-ACGI				0,1					
	o-effect conc		NEC						
	ue in fresh wa						0,0763		mg/l
	ue in marine v						0,011		mg/l
	ue for fresh w						0,275		mg/kg
	ue for marine						0,0396		mg/kg
	ue for water, i						0,763		mg/l
	ue of STP mic						3,6		mg/l
Normal val	ue for the terr	estrial compa	artment				0,015		mg/kg
Health - De	Effects on consumers	ect level - Dl	NEL / DMEL		Effects on workers				
Route of	Acute local	Acute	Chronic	Chronic	Acute local	Acı	ute	Chronic	Chronic
exposure		systemic	local	systemic		sys	temic	local	systemic
Oral		30 mg/kg bw/d		9,1 mg/kg bw/d					
Inhalation	295 mg/m3	295 mg/m3	1,03	1,03		590) mg/m3	2,06	2,06
			mg/m3	mg/m3				mg/m3	mg/m3
Skin	1,124	200 mg/kg	0,051	9,1 mg/kg	2,848) mg/kg	0,102	18,2 mg/kg
	mg/cm2	bw/d	mg/cm2	bw/d	mg/cm2	bw/	/d	mg/cm2	bw/d
SODIUM SIL									
Predicted n	o-effect conc	entration - Pl	NEC						
Normal val	ue in fresh wa	ater					7,5		mg/l
Normal val	ue for marine	water sedim	ent				1		mg/l
Normal val	ue for water, i	ntermittent re	elease				7,5		mg/l
Normal val	ue of STP mic	croorganisms	;				348		mg/l
Health - De	Effects on consumers	ect level - Dl	NEL / DMEL		Effects on workers				
Route of	Acute local	Acute	Chronic	Chronic	Acute local	Acı	ute	Chronic	Chronic
exposure		systemic	local	systemic		sys	temic	local	systemic
Oral			VND	0,80 mg/kg bw/d					
Inhalation			VND	1,38 mg/m3				VND	5,61 mg/m3
Skin			VND	0,8 mg/kg				VND	1,59 mg/kg



Date: 06/12/2018

Product name: Bottle Blonde Powder Lightener

Version no.: 2 Date of revision: 20/07/2020

DISODIUM	METASILIC	ATE								
Health - Derived no-effect level - DNEL / DMEL										
	Effects on Effects on									
	consumers				workers					
Route of	Acute local	Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic		
exposure		systemic	local	systemic		systemic	local	systemic		
Oral				0,74 mg/kg bw/d						
Inhalation				1,55		6,22		6,22		
				mg/m3				mg/m3		
Skin				0,74 mg/kg				1,49 mg/kg		
				bw/d				bw/d		
SODIUM P	ERSULFATE									
Threshold										
Туре		C	Country	TWA/8h		STEL/1	5min			
. , , , , , , , , , , , , , , , , , , ,			Joanny	mg/m3	ppm	0122,1		ppm		
VLA		F	ESP	0,1						
TLV-ACGI				0,1						
	no-effect conc	entration - P	NEC	•, •						
Normal val	ue in fresh wa	ater				0,0763		mg/l		
Normal val	ue in marine v	water				11		mg/l		
Normal val	ue for fresh w	ater sedimer	nt			0,275		mg/kg		
Normal val	ue for marine	water sedim	ent			0,396		mg/kg		
Normal val	ue for water, i	intermittent re	elease			0,763		mg/l		
Normal val	ue of STP mid	croorganisms	6			3,6		mg/l		
	ue for the terr					0,015		mg/kg		
	erived no-eff			_		,		00		
	Effects on			_	Effects on					
	consumers				workers					
Route of	Acute local	Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic		
exposure		systemic	local	systemic		systemic	local	systemic		
Oral		30 mg/kg bw/d		9,1 mg/kg bw/d						
Inhalation	295 mg/m3	295 mg/m3	1,03	1,03		590 mg/m3	2,06	2,06		
		-	mg/m3	mg/m3		c	mg/m3	mg/m3		
Skin	1,124	200 mg/kg	0,051	9,1 mg/kg	2,848	400 mg/kg	0,102	18,2 mg/kg		
	mg/cm2	bw/d	mg/cm2	bw/d	mg/cm2	bw/d	mg/cm2	bw/d		

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.



Version no.: 2 Date of revision: 20/07/2020

Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Section 9: Physical and Chemical Properties

Appearance Colour Odour Powder Grey Characteristic



Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener Version no.: 2 Date of revision: 20/07/2020

Odour threshold pH	Not available 9,8 – 10,8
Melting Point / Freezing point	Not available
Initial Boiling point	Not available
Boiling point	Not available
Flash Point (°C)	Not available
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	Not available
Solubility in Water	Not available
Partition coefficient: n-ctanol/water	Not available
Auto-ignition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

Section 10: Stability and Reactivity

Reactivity	There are no particular risks of reaction with other substances in normal conditions of use.
	DISODIUM METASILICATE
	The aqueous solutions act as: strong bases.
	<u>SODIUM PERSULFATE</u> Decomposes at temperatures above 145°C/293°F.
	With water it reduces to bisulphate with the development of oxygen.
Chemical stability	The product is stable in normal conditions of use and storage.



Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener Version no.: 2 Date of revision: 20/07/2020

Possibility of hazardous reactions	The powders are potentially explosive when mixed with air.
	DISODIUM METASILICATE
	May react dangerously with fluorine, lithium.
	SODIUM PERSULFATE
	Reacts violently with combustible substances, reducing
	substances. Fire hazard. Possibility of explosion.
Conditions to avoid	Avoid environmental dust build-up.
Incompatible materials	DISODIUM METASILICATE
	The aqueous solution is incompatible with acids, organic anhydrides, acrylates, alcohols, aldehydes, alkyl oxides, cresols, caprolactam, epichlorohydrin, ethylene dichloride, glycols, isocyanates, ketones, nitrates, phenols, vinyl acetate.
Hazardous	SODIUM PERSULFATE
decomposition products	May develop: sulphur oxides, oxygen.

Section 11: Toxicological Information

Information on toxicological effects

Metabolism, toxicokinetic, mechanism of action and other information	Information not available
Information on likely routes of exposure	Information not available
Delayed and immediate effects as well as chronic effects from short and long- term exposure	Information not available
Interactive effects	Information not available
ACUTE TOXICITY	LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component)
	LD50 (Inhalation – mists / powders) of the mixture:



Page 13 of 23

Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener Version no.: 2 Date of revision: 20/07/2020

	Not classified (no significant component)
	LD50 (Oral) of the mixture: 949 mg/kg
	LD50 (Dermal) of the mixture: Not classified (no significant component)
SODIUM PERSULFATE	LD50 (Oral) 895 mg/kg Rat LD50 (Dermal) > 10000 mg/kg Coniglio LC50 (Inhalation) 5,1 mg/l/4h Rat
SODIUM SILICATE	LD50 (Oral) 3400 mg/ kg (rat) LD50 (Dermal) > 5000 mg/kg (rat) LC50 (Inhalation) > 2,06 g/m3 (rat)
DIPOTASSIUM PEROXODISULPHATE	LD50 (Oral) 1130 mg/kg (ratto) LD50 (Dermal) > 10000 mg/kg (coniglio) LC50 (Inhalation) > 42,9 mg/l (ratto)
DISODIUM METASILICATE	LD50 (Oral) 1152 mg/kg bw (Ratto) LD50 (Dermal) > 5000 mg/kg bw (Ratto) LC50 (Inhalation) > 2,06 g/m3 (Ratto)
AMMONIUM PEROXYDISULPHATE	LD50 (Oral) 272 mg/kg Rat LD50 (Dermal) > 2000 mg/kg Rat LC50 (Inhalation) > 5,1 mg/l/4h Rat
SKIN CORROSION / IRRITATION	Corrosive for the skin
SERIOUS EYE DAMAGE / IRRITATION	Causes serious eye damage
RESPIRATORY OR SKIN SENSITISATION	Sensitising for the skin Sensitising for the respiratory system
GERM CELL MUTAGENICITY	Does not meet the classification criteria for this hazard class
CARCINOGENICITY	Does not meet the classification criteria for this hazard class



Date of revision: 20/07/2020

Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener

REPRODUCTIVE TOXICITY	Does not meet the classification criteria for this hazard class
STOT - SINGLE EXPOSURE	May cause respiratory irritation
STOT - REPEATED EXPOSURE	Does not meet the classification criteria for this hazard class
ASPIRATION HAZARD	Does not meet the classification criteria for this hazard class

Section 12: Eco-toxicity Information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

Toxicity

SODIUM PERSULFATE LC50 - for Fish 163 mg/l/96h Oncorhynchus mykiss (Trota iridea) EC50 - for Crustacea 133 mg/l/48h Daphnia magna EC50 - for Algae / Aquatic Plants 116 mg/l/72h Metodo: OECD TG 201 EC10 for Algae / Aquatic Plants 36 mg/l/18h Chronic NOEC for Algae / Aquatic Plants < 171 mg/l Pseudokirchneriella subcapitata (alghe cloroficee) SODIUM SILICATE LC50 - for Fish 1108 mg/l/96h (Brachydanio rerio) EC50 - for Crustacea 1700 mg/l/48h (Daphnia magna) DIPOTASSIUM PEROXODISULPHATE LC50 - for Fish 107,6 mg/l/96h Scophthalmus maximus EC50 - for Crustacea 120 mg/l/48h (daphnia) EC50 - for Algae / Aquatic Plants 320 mg/l/72h Phaeodactylum **DISODIUM METASILICATE** LC50 - for Fish 1108 mg/l/96h (Brachydanio rerio) 1700 mg/l/48h (Daphnia magna) EC50 - for Crustacea EC50 - for Algae / Aquatic Plants 207 mg/l/72h (Schenedesmus subspicatus)



Page 15 of 23

Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener Version no.: 2 Date of revision: 20/07/2020

AMMONIUM PEROXYDISULPHATE LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants EC10 for Algae / Aquatic Plants	107,6 mg/l/96h Scophthalmus maximus 120 mg/l/48h (Daphnia magna) 320 mg/l/72h Phaeodactylum 36 mg/l/72h Pseudomonas putida
Persistence and degradability	
SODIUM PERSULFATE Solubility in water Degradability: information not available	730 g/l
DIPOTASSIUM PEROXODISULPHATE Rapidly degradable	
DISODIUM METASILICATE Solubility in water Degradability: information not available	210000 mg/l
AMMONIUM PEROXYDISULPHATE Solubility in water Degradability: information not available	> 10000 mg/l
Bio accumulative potential	Information not available
Mobility in soil	Information not available
Results of PBT and vPvB assessment	On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.
Other adverse effects	Information not available

Section 13: Disposal Considerations

Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.



Page 16 of 23

Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener Version no.: 2 Date of revision: 20/07/2020

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Section	14:	Trans	port	Information
---------	-----	-------	------	-------------

UN number

IATA:

ADR / RID, IMDG, IATA: 3085

UN proper shipping name

ADR / RID:	OXIDIZING SOLID, CORROSIVE, N.O.S.
IMDG:	OXIDIZING SOLID, CORROSIVE, N.O.S.
IATA:	OXIDIZING SOLID, CORROSIVE, N.O.S.

NO

Transport hazard class(es)

Class: 5.1		Label: 5.1 (8)	5.1	
Class: 5.1		Label: 5.1 (8)	51	
Class: 5.1		Label: 5.1 (8)	5.1	
			V	V
IATA:	111			
zards				
	NO			
	NO			
	Class: 5.1	Class: 5.1 Class: 5.1 IATA: III zards NO	Class: 5.1 Label: 5.1 (8) Class: 5.1 Label: 5.1 (8) IATA: III zards	Class: 5.1 Label: 5.1 (8)



Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener

Special precautions for user			
ADR / RID:	HIN - Kemler: 58 Special Provision: -	Limited Quantities: 5 kg	Tunnel restriction code: (E)
IMDG:	EMS: F-A, S-Q	Limited Quantities: 5 kg	
IATA:	Cargo:	Maximum quantity: 100 Kg	Packaging instructions: 563
	Pass.:	Maximum quantity: 25 Kg	Packaging instructions: 559
	Special Instructions:	A3	
Transport in bulk according to Annex II of Marpol and the IBC Code	Information not relev	vant	

Section 15: Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P8

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point

65

AMMONIUM PEROXYDISULPHATE Reg. no.: 01-2119495973-19-0000



None

None

None

Version no.: 2 Date of revision: 20/07/2020

Product name: Bottle Blonde Pov	/der Lightener
Substances in Candidate List (Art. 59 REACH)	On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.
Substances subject to authorisation (Annex XIV REACH)	None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

Substances subject to the Rotterdam Convention:

Date: 06/12/2018

Substances subject to the Stockholm Convention:

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Restrictions relating to the product or contained substances pursuant to SUSMP - Posions Schedule dated 9 July 2020

Contained substance

SODIUM PERSULFATE

CAS 7775-27-1

Schedule 6 Labelling requirements apply in hair preparations

FIRST AID INSTRUCTIONS

For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once). If swallowed, do NOT induce vomiting.



Date: 06/12/2018 Product name: Bottle Blonde Powder Lightener Version no.: 2 Date of revision: 20/07/2020

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor, or for at least 15 minutes.

WARNING – This product contains ingredients which may cause skin irritation to certain individuals. A preliminary test according to accompanying directions should be made before use. This product must not be used for dyeing eyelashes or eyebrows; to do so may be injurious to the eye. Do not use on broken skin. Wash hands thoroughly after use.

Avoid contact with eyes.

Wear protective gloves when mixing or using.

Keep away from heat, sparks and naked flames.

Mix strictly according to instructions.

May cause fire if it comes into contact with other chemicals, paper or other flammable materials.

DIPOTASSIUM PEROXODISULPHATE

CAS 7727-21-1 Listed as POTASSIUM PERSULFATE

Schedule 6 Labelling requirements apply in hair preparations

FIRST AID INSTRUCTIONS

For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once).

If swallowed, do NOT induce vomiting.

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor, or for at least 15 minutes.

WARNING – This product contains ingredients which may cause skin irritation to certain individuals. A preliminary test according to accompanying directions should be made before use. This product must not be used for dyeing eyelashes or eyebrows; to do so may be injurious to the eye. Do not use on broken skin. Wash hands thoroughly after use.

Avoid contact with eyes. Wear protective gloves when mixing or using. Keep away from heat, sparks and naked flames. Mix strictly according to instructions.



Version no.: 2 Date of revision: 20/07/2020

May cause fire if it comes into contact with other chemicals, paper or other flammable materials.

AMMONIUM PEROXYDISULPHATE

CAS 7727-54-0 Listed as AMMONIUM PERSULFATE

Schedule 6 Labelling requirements apply in hair preparations

FIRST AID INSTRUCTIONS

For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once).

If swallowed, do NOT induce vomiting.

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor, or for at least 15 minutes.

WARNING – This product contains ingredients which may cause skin irritation to certain individuals. A preliminary test according to accompanying directions should be made before use. This product must not be used for dyeing eyelashes or eyebrows; to do so may be injurious to the eye. Do not use on broken skin. Wash hands thoroughly after use.

Avoid contact with eyes.

Wear protective gloves when mixing or using.

Keep away from heat, sparks and naked flames.

Mix strictly according to instructions.

May cause fire if it comes into contact with other chemicals, paper or other flammable materials.

Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

Section 16: Other Information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Ox. Sol. 3Oxidising solid, category 3Met. Corr. 1Substance or mixture corrosive to metals, category 1



Date o

Version no.: 2 Date of revision: 20/07/2020

Date: 06/12/2018

Product name: Bottle Blonde Powder Lightener

Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing
	difficulties if inhaled.
H317	May cause an allergic skin reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration



Date: 06/12/2018

Product name: Bottle Blonde Powder Lightener

Version no.: 2 Date of revision: 20/07/2020

- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value

- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.

- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy



Version no.: 2 Date of revision: 20/07/2020

Note for users:

Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Disclaimer:

The information continued herein is based on the manufacturers own study and the work of others, implied, as to the accuracy, completeness or adequacy of the information contained herein, and neither the provider nor the manufacturer are liable to any party for any damages of any nature, including direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of any information in the SDS, or in any other way related (directly or indirectly)to this SDS. The information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any other process

End of document